





Culligan of Greater Kansas City culligankc.com 913.782.4141





With it's smooth classic lines the Mougl cooler will compliment any décor. The contoured drip tray enhances the shape of the cabinet and conveniently holds a cup or glass for hands-free filling.



Child-proof hot water faucet



Hot water On and Off switch



Hermetically sealed reciprocating Compressor



Cup Dispenser

DryGuard W

Crystal Mountain's patented DryGuard^{an} optional feature on all bottle-water coolers and is standard on certain models.

Molded from polypropylene, this sealed system protects your floors against leaks caused by created and faulty bottles.



Culligan of Greater Kansas City culligankc.com 913.782.4141



Performance & Specifications

Model: Hot & Cold; Cook & Cold

General:

Air cooled, bottle type water cooler provided with a power supply cord for connection to source of power supply.

Cooler Cabinet:

Blow molded, high density polyethylene (HDPE) resistent to cracking Available in white, granite and black colours

Faucet Type:

Concealed faucet for optimum hygiene Constructed of FDA approved nylon and silicon tubing. Optional child lock safety function.

Cold Water Tank Specifications:

Stainless steel 304 or HDPE casing with 2.0L volume Cold water cooling capacity of 3.5L/hr based on 21°C(69.8°F) room temperature

Cold Water Thermostat:

Preset at factory to dispense water at temperature from 6-10°C(43-50°F)
Adjustable cold control located at the back of the cabinet

Hot Water Tank Specifications:

Stainless steel 304 casing with 1.8L volume
Hot water capacity of 4.8L/hr based on 21°C(69.8°F) room temperature

Hot Water Thermostats and Heater:

Automatic thermostat control with temperature range of 75-92° C(167-197°F)
Manual safety reset in case of automatic thermostat failure
450W external mica-heater band
ON/OFF switch is located at the back of the cabinet
Electronic thermostat system(ETS) is available, which provides for a
temperature control range of 88-92°C(190.4-197°F)

Compressor Type:

Hermetically sealed reciprocating compressor (220V~240VAC /50Hz) (110~115V - 60Hz)

Refrigerant Type:R134a(CFC Free)

Refrigerant Charge:10z

Weight: H&C:13.8kg(30.5lbs.); C&C:12.8kg(28.3lbs)

Dimensions:

325mm deepx315mm widex985mm high (12.8in. deepx12.4in. widex38.8 in. high)

20FT Container Quantity: 252 UNITS 40FT Container Quantity: 518 UNITS

Packaging:

333mm deepx323mm widex1001mm high (13.1in. deepx12.8in. widex39.5in. high)

Culligan of Greater Kansas City culligankc.com 913.782.4141

